



## SLIDE GATE OPENER LOW VOLTAGE KIT GLD-GO-LV



**SUITABLE FOR SLIDE GATES  
UP TO 12 METRES**



**LIGHT COMMERCIAL / HEAVY  
RESIDENTIAL GATE OPENER**

## KEY FEATURES

### SUITABLE FOR SLIDE GATES

Suited for Slide Gates up to 12 metres

### MYQ CAPABLE

Opener is myQ capable for gates with an additional purchase of Safety IR Beams & myQ Gateway.<sup>1</sup>

### BATTERY BACKUP COMPATIBLE

Opener is Battery Backup compatible with additional purchase of Battery Backup accessory.<sup>2</sup>



Compliant to Australian and New Zealand Standard AS/NZS 60335.2.103



**x4**

## SMART



**MYQ CAPABLE TECHNOLOGY** lets users create schedules, monitor, receive alerts and control the gate opener away from home.<sup>1</sup>



**LCD DISPLAY** for fast and intuitive programming setup.



**SOFT-START AND SOFT-STOP** for smooth operation.



**SPEED ADJUSTMENT** allows you to increase and decrease opening and closing gate speeds.



**PEDESTRIAN MODE** allows for customised gate opening access.

## QUIET & RELIABLE



**24V LOW VOLTAGE**



**3-YEAR WARRANTY**



**IP44 WEATHER RESISTANT** Ingress protection IP44 suitable for outdoor installation.



**QUIET DC MOTOR** eliminates noise and vibrations, providing smooth operation.



**BATTERY BACKUP** ensures access even when the power is out.<sup>2</sup>



**SLIDING GATES UP TO 12 METRES**

## SAFE & SECURE



**SECURITY+ 2.0®** sends a new code with every remote click.



**PREMIUM AUTOMATIC SAFETY REVERSE** function will allow your gate to stop and reverse automatically if obstructed during opening or closing.



**TIMER-TO-CLOSE** automatically closes the gate after a pre-set amount of time.<sup>3</sup>



**IMPROVED TRANSMITTER RANGE** has up to 18% better range meaning you can start opening your gate sooner.<sup>4</sup>



**AUTOMATIC FORCE SENSING** monitors and adjusts the force needed to open your gate with each operation.



**DISENGAGEMENT MECHANISM** allows you to manually open the gate whenever needed.

## Accessories Included



### Four Button Remote Controls

Premium remotes to control up to 4 garage doors or gates. Each button can be programmed to Security+ and Security+2.0 devices.

**EB60G**

## Powerful Add-Ons



### Gate myQ Connectivity Bundle

Add monitoring and control away from home. Includes myQ Gateway and The Outdoor Protector System (Safety IR Beams).

**M828AU772**



### Battery Backup

Get in and out when the power's out with Battery Backup. Batteries fit within the housing of the opener.

**MGBBU**



### Wireless Security Keypad

Convenient and safe access to open and close your gate without using a remote control or key.

**EB50G**



### E-Lock for Horizontal Installation

For additional security with electric lock. Includes 3 keys.

**ELOCK-H**



### E-Lock for Vertical Installation

For additional security with electric lock. Includes 3 keys.

**ELOCK-V**



### Mag-Lock

Additional security with magnetic lock.

**MC-485AU**



### Slide Gate Stop

Additional security for slide gates.

**002A2332**



### Rack

Additional 1m racking.

**MSS-RACK**



### Outdoor Protector System

Safety IR Beams for outdoor gate applications (IP44).

**772ANZ**

**grifco.com.au • grifco.co.nz**

<sup>1</sup> Additional purchase of Grifco myQ Gateway and Safety IR Beams accessories required to enable myQ functionality. Visit [grifco.com.au](http://grifco.com.au) for further information. <sup>2</sup> Additional purchase of Grifco Battery Backup accessory required to enable Battery Backup functionality. Visit [grifco.com.au](http://grifco.com.au) for further information.

<sup>3</sup> Safety IR Beams must be installed to enable the use of Timer-to-Close. See User Guide for additional information. <sup>4</sup> When compared to other available products.



## SLIDE GATE OPENER LOW VOLTAGE KIT GLD-GO-LV



**SUITABLE FOR SLIDE GATES  
UP TO 12 METRES**




**LIGHT COMMERCIAL / HEAVY  
RESIDENTIAL GATE OPENER**

### Start with smart. Compatible with myQ<sup>2</sup>

Additional purchase of  
The Outdoor Protector System  
and myQ Gateway is required



### TYPICAL INSTALLATION - SLIDE GATES



1. Gate Opener (GGS1000)
2. Limit Switch Brackets
3. Transformer Box (MGTR3-120VA)  
mounted near 240 V power supply.
4. Remote Control (E960G)

- Maximum Weight for single gate: 1000kg
- Maximum Width for single gate: 12m

#### FOR SLIDING GATES

- Monitor and control your gate away from home through the myQ App.
- Peace of mind knowing if gate is open or closed anywhere and any time.
- Receive real time alerts and notifications so you know when the gate is opened or closed by loved ones.
- Pre-set times to automatically close your gate at any time.
- See history records of your gate open and close periods.
- Protect your loved ones and belongings with The Outdoor Protector System (Safety IR Beams).
- Compatible myQ App available for smart devices including Apple Watch.

APP AVAILABLE ON:



## SECURITY



#### SECURITY+ 2.0<sup>\*</sup>

- Encrypted rolling code across multiple frequencies.
- Security+ 2.0<sup>\*</sup> technology virtually eliminates interference.

## SMART



#### RADIO

- Provides 2-way communication from gate openers and accessories.
- Receiver with 64 memory register.

## Standard Specifications

- Main AC Supply: 220-240VAC; 50/60Hz
- Motor Voltage: 24 VDC
- Input Power: 150 W
- Ambient Temperature Range: -20-+55°C
- Maximum Pull Force: 800 N
- Maximum Torque: 22.5 Nm
- Radio frequency: 433.30, 433.92, 434.54 MHz with Security+ 2.0 technology
- Compatible with myQ Technology<sup>1</sup>
- Gate Opener Capacity of up to 64 memory registers

## GRIFCO<sup>®</sup>

#### AUSTRALIA

Chamberlain Australia Pty Ltd  
PO Box 1446  
North Ryde NSW 2113

**www.grifco.com.au**  
**1800 GRIFCO**

#### NEW ZEALAND

Chamberlain New Zealand Limited  
17B Arrenway Drive  
Rosedale 0632, Auckland

**www.grifco.co.nz**  
**0800 653 667**

Designed & Engineered in Australia  
© 2023 The Chamberlain Group LLC. All Rights Reserved. \* Registered Trade Marks of The Chamberlain Group, Inc. <sup>TM</sup> Trade Marks of Chamberlain Group, Inc.



#### WARNING!

Product contains coin/button cell batteries. The battery is hazardous. Keep product and batteries away from children. Battery can cause severe or fatal injuries in 2 hours or less if swallowed or placed inside any part of the body. Seek immediate medical attention if it is suspected that a coin/button cell battery has been swallowed or placed inside any part of the body.

<sup>1</sup> This feature requires monitored Safety IR Beams to be fitted. Linking your myQ account to partner may require an additional accessory purchase or subscription fee. Apple, the Apple logo, iPhone, and iPad are trademarks of Apple Inc., registered in the U.S. and other countries and regions. App Store is a service mark of Apple Inc. Google Play and the Google Play logo are trademarks of Google LLC. Smartphone not included.